

RG 800 SERIES STEEL/ STAINLESS STEEL UNIFORMLY DISTRIBUTED LOAD (UDL) X > 75% INSTALTION LENGTH (BB)

ROLLER BB	30DIA X 1.5	40DIA X 1.5	50DIA X 1.5				51DIA X 2				60DIA X 2		
	6, 8, 10	8, 10, 11, 11H, 12	8	10	11, 11H	12	8	10	11, 11H	12	10	11, 11H	12
100	12	30	100	100	100	100	100	100	100	100	100	100	100
200	12	30	100	100	100	100	100	100	100	100	100	100	100
300	12	30	97	100	100	100	97	100	100	100	100	100	100
400	12	30	72	100	100	1000	72	100	100	1000	100	100	100
500	12	30	57	100	100	100	57	100	100	100	100	100	100
700	12	30	40	100	100	100	40	100	100	100	100	100	100
800	12	30	35	92	100	100	35	92	100	100	88	100	100
900	12	30	31	82	100	100	31	82	100	100	78	100	100
1000	9	30	28	75	86	86	28	75	86	86	71	100	100
1200	-	-	24	49	49	49	24	49	49	49	59	87	87
1400	-	-	20	31	31	31	20	31	31	31	51	54	54
1500	-	-	19	25	25	25	19	25	25	25	44	44	44
	RG-30	RG-40	RG-50				RG-50MD				RG-60		

IMPORTANT: Load Capacity calculated on evenly placed item, without impact, equal to or greater than 75% of BB.

If in doubt ASK